Скелет синтаксического плагина

syntax.php

```
<?php
/**
 * Plugin Skeleton: Displays "Hello World!"
 *
 * Syntax: <TEST> - will be replaced with "Hello World!"
 *
 * @license    GPL 2 (http://www.gnu.org/licenses/gpl.html)
 * @author     Christopher Smith <chris@jalakai.co.uk>
 */

if(!defined('DOKU_INC'))
define('DOKU_INC',realpath(dirname(__FILE__).'/../../').'/');
if(!defined('DOKU_PLUGIN'))
define('DOKU_PLUGIN',DOKU_INC.'lib/plugins/');
require_once(DOKU_PLUGIN.'syntax.php');

/**
 * All DokuWiki plugins to extend the parser/rendering mechanism
 * need to inherit from this class
 */
class syntax_plugin_test extends DokuWiki_Syntax_Plugin {

   /**
    * Get an associative array with plugin info.
    *
    * <p>
    * The returned array holds the following fields:
    * <dl>
    * <dt>author</dt><dd>Author of the plugin</dd>
    * <dt>email</dt><dd>Email address to contact the author</dd>
    * <dt>date</dt><dd>Last modified date of the plugin in
    * <tt>YYYY-MM-DD</tt> format</dd>
    * <dt>name</dt><dd>Name of the plugin</dd>
    * <dt>desc</dt><dd>Short description of the plugin (Text only)</dd>
    * <dt>url</dt><dd>Website with more information on the plugin
    * (eg. syntax description)</dd>
    * </dl>
    * @param none
    * @return Array Information about this plugin class.
    * @public
    * @static
    */
    function getInfo(){
        return array(
            'author' => 'me',
```

```
            'email'  => 'me@somewhere.com',
            'date'   => '20yy-mm-dd',
            'name'   => 'Test Plugin',
            'desc'   => 'Testing 1, 2, 3...',
            'url'    => 'http://www.dokuwiki.org/plugin:test',
        );
    }

   /**
    * Get the type of syntax this plugin defines.
    *
    * @param none
    * @return String <tt>'substition'</tt> (i.e. 'substitution').
    * @public
    * @static
    */
    function getType(){
        return 'substition';
    }

    /**
     * What kind of syntax do we allow (optional)
     */
//    function getAllowedTypes() {
//        return array();
//    }

   /**
    * Define how this plugin is handled regarding paragraphs.
    *
    * <p>
    * This method is important for correct XHTML nesting. It returns
    * one of the following values:
    * </p>
    * <dl>
    * <dt>normal</dt><dd>The plugin can be used inside paragraphs.</dd>
    * <dt>block</dt><dd>Open paragraphs need to be closed before
    * plugin output.</dd>
    * <dt>stack</dt><dd>Special case: Plugin wraps other
paragraphs.</dd>
    * </dl>
    * @param none
    * @return String <tt>'block'</tt>.
    * @public
    * @static
    */
//    function getPType(){
//        return 'normal';
//    }
```

```
    /**
     * Where to sort in?
     *
     * @param none
     * @return Integer <tt>6</tt>.
     * @public
     * @static
     */
     function getSort(){
         return 999;
     }


    /**
     * Connect lookup pattern to lexer.
     *
     * @param $aMode String The desired rendermode.
     * @return none
     * @public
     * @see render()
     */
     function connectTo($mode) {
       $this->Lexer->addSpecialPattern('<TEST>',$mode,'plugin_test');
//       $this->Lexer->addEntryPattern('<TEST>',$mode,'plugin_test');
     }

//    function postConnect() {
//       $this->Lexer->addExitPattern('</TEST>','plugin_test');
//    }


    /**
     * Handler to prepare matched data for the rendering process.
     *
     * <p>
     * The <tt>$aState</tt> parameter gives the type of pattern
     * which triggered the call to this method:
     * </p>
     * <dl>
     * <dt>DOKU_LEXER_ENTER</dt>
     * <dd>a pattern set by <tt>addEntryPattern()</tt></dd>
     * <dt>DOKU_LEXER_MATCHED</dt>
     * <dd>a pattern set by <tt>addPattern()</tt></dd>
     * <dt>DOKU_LEXER_EXIT</dt>
     * <dd> a pattern set by <tt>addExitPattern()</tt></dd>
     * <dt>DOKU_LEXER_SPECIAL</dt>
     * <dd>a pattern set by <tt>addSpecialPattern()</tt></dd>
     * <dt>DOKU_LEXER_UNMATCHED</dt>
     * <dd>ordinary text encountered within the plugin's syntax mode
     * which doesn't match any pattern.</dd>
     * </dl>
```

```
    * @param $aMatch String The text matched by the patterns.
    * @param $aState Integer The lexer state for the match.
    * @param $aPos Integer The character position of the matched text.
    * @param $aHandler Object Reference to the Doku_Handler object.
    * @return Integer The current lexer state for the match.
    * @public
    * @see render()
    * @static
    */
    function handle($match, $state, $pos, &$handler){
        switch ($state) {
          case DOKU_LEXER_ENTER :
            break;
          case DOKU_LEXER_MATCHED :
            break;
          case DOKU_LEXER_UNMATCHED :
            break;
          case DOKU_LEXER_EXIT :
            break;
          case DOKU_LEXER_SPECIAL :
            break;
        }
        return array();
    }

   /**
    * Handle the actual output creation.
    *
    * <p>
    * The method checks for the given <tt>$aFormat</tt> and returns
    * <tt>FALSE</tt> when a format isn't supported. <tt>$aRenderer</tt>
    * contains a reference to the renderer object which is currently
    * handling the rendering. The contents of <tt>$aData</tt> is the
    * return value of the <tt>handle()</tt> method.
    * </p>
    * @param $aFormat String The output format to generate.
    * @param $aRenderer Object A reference to the renderer object.
    * @param $aData Array The data created by the <tt>handle()</tt>
    * method.
    * @return Boolean <tt>TRUE</tt> if rendered successfully, or
    * <tt>FALSE</tt> otherwise.
    * @public
    * @see handle()
    */
    function render($mode, &$renderer, $data) {
        if($mode == 'xhtml'){
            $renderer->doc .= "Hello World!";            // ptype =
'normal'
//            $renderer->doc .= "<p>Hello World!</p>";     // ptype =
'block'
```

```
            return true;
        }
        return false;
    }
}

//Setup VIM: ex: et ts=4 enc=utf-8 :
?>
```

Замечание

Имя этого плагина — «test». You can see that by the name of the class: `syntax_plugin_test` — everything following `syntax_plugin_` is taken as the name of the plugin.

Т. к. имя плагина — «test», то и храниться он должен в папке `lib/plugins/test` для автоматического определения движком «ДокуВики». Имя файла должно быть «syntax.php».

From:
https://wwoss.ru/ - **worldwide open-source software**

Permanent link:
https://wwoss.ru/doku.php?id=wiki:devel:syntax_plugin_skeleton&rev=1724651690

Last update: **2024/08/26 08:54**