

XML-RPC

XML-RPC is one of the available protocols to access DokuWiki's [Remote API](#).

The API implements the [Wiki RPC Interface 2.0 Specifications](#) (web.archive.org) in the `wiki.*` namespace and adds additional DokuWiki specific calls in the `dokuwiki.*` namespace.

Plugins can add their own calls to the API using [Remote Plugin components](#).

Note: there is also a [JSON-RPC](#) API which provides the same functionality but is based on JSON rather XML.

Get It Working

1. Set the [remote](#) option to enable XML-RPC in the Configuration Settings «Authentication» section
2. Set the [remoteuser](#) option with a mix of comma separated «usernames,groups»
3. For security reasons it's safer to allow access to the XML-RPC over HTTPS only. DokuWiki's `.htaccess.dist` contains some rewrite rules to do that.
4. You might need to install an XML package like `php-xml` (on debian)

Accessing The XML-RPC Interface

You can access the XML-RPC interface via the following URLs:

```
http://<your wiki/domain/ip>/lib/exe/xmlrpc.php
```

or

```
https://<your wiki/domain/ip>/lib/exe/xmlrpc.php
```

Here are some [Samples of Clients using the XML-RPC Api](#) to test with

Sample XML Requests

You should use an XML-RPC library instead of hand-crafting your requests.

Here is an example of how to post to the API:

```
POST /RPC2 HTTP/1.0
User-Agent: Frontier/5.1.2 (WinNT)
Host: betty.userland.com
Content-Type: text/xml
Content-length: 181
```

```
<?xml version="1.0"?>
<methodCall>
  <methodName>examples.getStateName</methodName>
  <params>
    <param>
      <value>
        <i4>41</i4>
      </value>
    </param>
  </params>
</methodCall>
```

```
<?xml version="1.0"?>
<methodCall>
  <methodName>dokuwiki.getVersion</methodName>
</methodCall>
```

example put page

```
<?xml version="1.0"?>
<methodCall>
  <methodName>wiki.putPage</methodName>
  <params>
    <param>
      <value>
        <string>myputpage
        </string>
      </value>
    </param>
    <param>
      <value>
        <string>This is my page content</string>
      </value>
    </param>
    <param>
      <value>
        <struct>
          <member>
            <name>sum</name>
            <value><string>Spiceworks</string></value>
          </member>
          <member>
            <name>minor</name>
            <value><boolean>True</boolean></value>
          </member>
        </struct>
      </value>
    </param>
  </params>
</methodCall>
```

Available Functions

Functions are listed in the following format:

Name	The name of the function
Parameters	A list of parameters to pass to the function
Data	The type of the returned data
Description	Short explanation what the function does
Since	The DokuWiki (and XML-RPC API Version) this function was introduced

dokuwiki.getPagelist

Name	dokuwiki.getPagelist
Parameters	(string) namespace, (array) options
Data	(array) list of page items
Description	Lists all pages within a given namespace. The options are passed directly to search_allpages() .
Since	2009-03-06 (1)

dokuwiki.getVersion

Name	dokuwiki.getVersion
Parameters	-
Data	(string) version number
Description	Returns the DokuWiki version of the remote Wiki.

dokuwiki.getTime

Name	dokuwiki.getTime
Parameters	-
Data	(int) timestamp
Description	Returns the current time at the remote wiki server as Unix timestamp.
Since	2009-03-06 (1)

dokuwiki.getXMLRPCAPIVersion

Name	dokuwiki.getXMLRPCAPIVersion
Parameters	-
Data	(int) version number
Description	Returns the XML RPC interface version of the remote Wiki. This is DokuWiki implementation specific and independent of the supported standard API version returned by <code>wiki.getRPCVersionSupported</code> .
Since	2009-03-06 (1)

dokuwiki.login

Name	dokuwiki.login
Parameters	(string) user, (string) password
Data	(boolean) login successful

Description	Uses the provided credentials to execute a login and will set cookies. This can be used to make authenticated requests afterwards. Your client needs to support cookie handling. Alternatively use HTTP basic auth credentials.
Since	2009-03-06 (1)

dokuwiki.search

Name	dokuwiki.search
Parameters	(string) a query string as described on search
Data	(array) associative array with matching pages similar to what is returned by dokuwiki.getPageList, snippets are provided for the first 15 results
Description	Performs a fulltext search.
Since	2010-02-28 (3)

dokuwiki.getTitle

Name	dokuwiki.getTitle
Parameters	-
Data	(string) the title of the wiki
Description	Returns the title of the wiki.
Since	2010-04-18 (4)

dokuwiki.appendPage

Name	dokuwiki.appendPage
Parameters	(string) pagename , (string) raw Wiki text, (array) attrs Where attrs can contain the following: \$attrs['sum'] = (string) change summary \$attrs['minor'] = (boolean) minor
Data	(boolean)
Description	Appends text to a Wiki Page.
Since	2010-11-20 (5)

dokuwiki.setLocks

Name	dokuwiki.setLocks
Parameters	(array) list of two lists of page ids ['lock' => [...], 'unlock' => [...]]
Data	(array) array with 4 lists of pageids ['locked' => [...], 'lockfail' => [...], 'unlocked' => [...], 'unlockfail' => [...]]
Description	Allows you to lock or unlock a whole bunch of pages at once. Useful when you are about to do an operation over multiple pages.
Since	2009-03-06 (1)

dokuwiki.createUser

Name	dokuwiki.createUser
Parameters	(array) parameters, where parameters can contain: <pre>\$params = ['user' => 'username', 'password' => 'password1', 'name' => 'User Name', 'mail' => 'user@example.com', 'groups' => ['user', 'test'], 'notify' => false]</pre>
Data	(bool) true if the user is created
Description	Create a user. Returns 400 range error codes if input is not accepted.
Since	2022-06-24

dokuwiki.deleteUsers

Name	dokuwiki.deleteUsers
Parameters	(array) list of usernames to delete
Data	(bool) true if the users were deleted
Description	Allows you to delete one or more users. Useful to implement GDPR right to be forgotten tools.
Since	2018-05-24

wiki.getRPCVersionSupported

Name	wiki.getRPCVersionSupported
Parameters	-
Data	(string) version number
Description	Returns 2 with the supported RPC API version.

wiki.aclCheck

Name	wiki.aclCheck
Parameters	(string) pagename
Data	(int) Permissions of given wiki page
Description	Returns the permission of the given wikipage.

wiki.getPage

Name	wiki.getPage
Parameters	(string) pagename
Data	(string) raw Wiki text
Description	Returns the raw Wiki text for a page.

wiki.getPageVersion

Name	wiki.getPageVersion
Parameters	(string) pagename , (int) Timestamp
Data	(string) raw Wiki text
Description	Returns the raw Wiki text for a specific revision of a Wiki page.

wiki.getPageVersions

Name	wiki.getPageVersions
Parameters	(string) pagename , (int) offset
Data	(array) each array item holds the following data: <pre>\$data['user'] = username \$data['ip'] = ip address \$data['type'] = type of change \$data['sum'] = summary \$data['modified'] = modification date as IXR_Date Object \$data['version'] = page version as timestamp</pre>
Description	Returns the available versions of a Wiki page. The number of pages in the result is controlled via the recent configuration setting. The offset can be used to list earlier versions in the history.

wiki.getPageInfo

Name	wiki.getPageInfo
Parameters	(string) pagename
Data	(array) an array containing the following data: <pre>\$data['name'] = [[:pagename]] \$data['lastModified'] = modification date as IXR_Date Object \$data['author'] = author of the Wiki page. \$data['version'] = page version as timestamp</pre>
Description	Returns information about a Wiki page.

wiki.getPageInfoVersion

Name	wiki.getPageInfoVersion
Parameters	(string) pagename , (int) timestamp
Data	(array) an array containing the following data: <pre>\$data['name'] = [[:pagename]] \$data['lastModified'] = modification date as UTC timestamp \$data['author'] = author of the Wiki page. \$data['version'] = page version as timestamp</pre>
Description	Returns information about a specific version of a Wiki page.

wiki.getPageHTML

Name	wiki.getPageHTML
Parameters	(string) pagename
Data	(string) rendered HTML

Description	Returns the rendered XHTML body of a Wiki page.
--------------------	---

wiki.getPageHTMLVersion

Name	wiki.getPageHTMLVersion
Parameters	(string) pagename , (int) timestamp
Data	(string) rendered HTML
Description	Returns the rendered HTML of a specific version of a Wiki page.

wiki.putPage

Name	wiki.putPage
Parameters	(string) pagename , (string) raw Wiki text, (array) attrs Where attrs can contain the following: \$attrs['sum'] = (string) change summary \$attrs['minor'] = (boolean) minor
Data	(boolean)
Description	Saves a Wiki Page.

wiki.listLinks

Name	wiki.listLinks
Parameters	(string) pagename
Data	(array) each array item holds the following data: \$data['type'] = local/extern \$data['page'] = the wiki page (or the complete URL if extern) \$data['href'] = the complete URL
Description	Returns a list of all links contained in a Wiki page.

wiki.getAllPages

Name	wiki.getAllPages
Parameters	-
Data	(array) One item for each page, each item containing the following data: \$data['id'] = id of the page \$data['perms'] = integer denoting the permissions on the page \$data['size'] = size in bytes \$data['lastModified'] = dateTime object of last modification date
Description	Returns a list of all Wiki pages in the remote Wiki.

wiki.getBackLinks

Name	wiki.getBackLinks
Parameters	(string) pagename
Data	(array)
Description	Returns a list of backlinks of a Wiki page.

wiki.getRecentChanges

Name	wiki.getRecentChanges
-------------	-----------------------

Parameters	(int) timestamp
Data	(array) each array item holds the following data: <code>\$data['name'] = page id</code> <code>\$data['lastModified'] = modification date as UTC timestamp</code> <code>\$data['author'] = author</code> <code>\$data['version'] = page version as timestamp</code>
Description	Returns a list of recent changes since given timestamp. As stated in recent_changes : Only the most recent change for each page is listed, regardless of how many times that page was changed.

wiki.getRecentMediaChanges

Name	wiki.getRecentMediaChanges
Parameters	(int) timestamp
Data	(array) each array item holds the following data: <code>\$data['name'] = media id</code> <code>\$data['lastModified'] = modification date as UTC timestamp</code> <code>\$data['author'] = author</code> <code>\$data['version'] = page version as timestamp</code> <code>\$data['perms'] = media permissions</code> <code>\$data['size'] = media size in bytes</code>
Description	Returns a list of recent changed media since given timestamp.

wiki.getAttachments

Name	wiki.getAttachments
Parameters	(String) namespace, (array) options
Data	(array) each array item holds the following data: <code>\$data['id'] = media id</code> <code>\$data['file'] = name of the file</code> <code>\$data['size'] = size in bytes</code> <code>\$data['mtime'] = upload date as a timestamp</code> <code>\$data['lastModified'] = modification date as XML-RPC Date object</code> <code>\$data['isimg'] = true if file is an image, false otherwise</code> <code>\$data['writable'] = true if file is writable, false otherwise</code> <code>\$data['perms'] = permissions of file</code>
Description	Returns a list of media files in a given namespace. The options are passed directly to search_media() .

wiki.getAttachment

Name	wiki.getAttachment
Parameters	(String) id
Data	(string) the data of the file, encoded in base64
Description	Returns the binary data of a media file.

wiki.getAttachmentInfo

Name	wiki.getAttachmentInfo
Parameters	(String) id

Data	(array) an array containing the following information about the file: <code>\$data['size'] = size in bytes</code> <code>\$data['lastModified'] = modification date as XML-RPC Date object</code>
Description	Returns information about a media file.

wiki.putAttachment

Name	wiki.putAttachment
Parameters	(String) id, (base64) data, (array) params Available parameters are: <code>\$params['ow'] = true</code> if file is to overwrite an already existing media object of the given id.
Data	
Description	Uploads a file as a given media id.

wiki.deleteAttachment

Name	wiki.deleteAttachment
Parameters	(String) id
Data	
Description	Deletes a file. Fails if the file is still referenced from any page in the wiki.

plugin.acl.listAcls

Name	plugin.acl.listAcls
Parameters	-
Data	(array) of ACLs {scope, user, permission}'
Description	Get the list of all ACLs.

plugin.acl.addAcl

Name	plugin.acl.addAcl
Parameters	(String) scope, (String) username, (int) permission
Data	(boolean) return true if the rule was correctly added
Description	Add an ACL rule. Use @groupname instead of user to add an ACL rule for a group.

plugin.acl.delAcl

Name	plugin.acl.delAcl
Parameters	(String) scope, (String) username
Data	(boolean) return true if the rules were correctly deleted
Description	Delete any ACL rule matching the given scope and user. Use @groupname instead of user to delete the ACL rules for the group.

Adding methods to the XML-RPC API

Use [Remote Plugins](#) to add other methods to the XML-RPC API.

A summary of recent plugins which indicate Remote support:

Name	Description	Remote plugins compatible with last two releases	
JSON Data Plugin	Build JSON database inside DokuWiki page and use the data in the page	1	json
struct Plugin	A new structured data plugin	1	struct

Σ 2 plugins matching query

To implement such a plugin please have a look at the [remote plugins development documentation](#).

XML-RPC Error Codes

Since XML-RPC API Version 7 (API Version 7 is since Release Adora Belle (2012-10-13)) useful hierarchical error codes have been introduced. The following error codes can be returned by the XML-RPC Interface:

Italic rows are just categories. Only normal printed rows are returned by the interface.

- *100 → Page errors*
 - *110 → Page access errors*
 - 111 → User is not allowed to read the requested page
 - 112 → User is not allowed to edit the page
 - 113 → manager permission is required
 - 114 → superuser permission is required
 - *120 → Page existence errors*
 - 121 → The requested page does not exist
 - *130 → Page edit errors*
 - 131 → Empty page id
 - 132 → Empty page content
 - 133 → Page is locked
 - 134 → Positive wordblock check
- *200 → Media errors*
 - *210 → Media access errors*
 - 211 → User is not allowed to read the requested media
 - 212 → User is not allowed to delete media
 - 215 → User is not allowed to list media
 - *220 → Media existence errors*
 - 221 → The requested media does not exist
 - *230 → Media edit errors*
 - 231 → Filename not given
 - 232 → File is still referenced
 - 233 → Could not delete file
- *300 → Search errors*
 - *310 → Argument errors*
 - 311 → The provided value is not a valid timestamp
 - *320 → Search result errors*
 - 321 → No changes in specified timeframe
- *400 → User management errors*
 - 401 invalid user name given

- 402 invalid user name given
- 403 invalid email address given

Additionally there are some server error codes that indicate some kind of server or XML-RPC failure. The codes are the following:

- -32600 → Invalid XML-RPC request. Not conforming to specification.
- -32601 → Requested method does not exist.
- -32602 → Wrong number of parameters or invalid method parameters.
- -32603 → Not authorized to call the requested method (No login or invalid login data was given).
- -32604 → Forbidden to call the requested method (but a valid login was given).
- -32605 → The XML-RPC API has not been enabled in the configuration
- -32700 → Parse Error. Request not well formed.
- -32800 → Recursive calls to system.multicall are forbidden.
- -99999 → Unknown server error.

Sample Clients

A number of [clients written in different languages](#) are available.

From:

<https://wwoss.ru/> - **worldwide open-source software**

Permanent link:

<https://wwoss.ru/doku.php?id=wiki:devel:xmlrpc>

Last update: **2025/01/15 10:29**

