

Мета-плагин

Совместим с «Докувики»

- 2024-02-06 "Kaos" **неизвестно**
- 2023-04-04 "Jack Jackrum" **неизвестно**
- 2022-07-31 "Igor" **да**
- 2020-07-29 "Hogfather" **да**



Установить метаданные для текущей страницы

Последнее обновление:

2024-08-07

Предоставляет

[Syntax](#)

Репозиторий

[исходный код](#)

Похож на [description](#), [htmlmetatags](#), [metaeditor](#), [metaheaders](#)

Теги: [!experimental](#), [meta](#)

- **Dokufreaks (previous authors: Michael Hamann, Esther Brunner, Gina Häußge, Michael Klier)**

- [include](#)
- [pagelist](#)
- [feed](#)
- [tag](#)
- [blog](#)
- [include](#)



экспериментальный



Description

This plugin allows you to set [metadata](#) for a page. This is useful for overriding default [DokuWiki](#) metadata, for example if you want to display someone else than the user who pasted the text into the wiki as the author of a [blog](#) entry.

Syntax

```
~~META:
key = value
~~
```

key	the metadata element to set	required
value	the metadata element content	required

You can set more than one element at once by using an & delimiter. Further, to set a child element, separate key and subkey with a space. Additional whitespace is allowed. Dates should be entered in the form YYYY-MM-DD hh:mm:ss. Two dates with an arrow (->) in between are considered as a period.

An example

```
~~META:
creator      = Esther Brunner
&date valid = 2006-04-15 -> 2006-10-15
~~
```

Data Structure

It is mandatory to use [Dublin Core element names](#) as keys for all metadata that might be interesting for external use. These are:

Element	Child Elements	Type	Comments
title	—	string	will be used for window title and links if <code>\$conf['useheading']</code> is on; defaults to the first heading
creator	—	string	indicates the primary author of a page; defaults to the full name of the user who created the page
subject	—	string	used by the blog plugin / tag component: list of space separated tags; not set by default
description	tableofcontents, abstract	array	tableofcontents is an array of the TOC items with keys <code>hid</code> (header ID), <code>title</code> , <code>type</code> and <code>level</code> ; abstract is 250 to 500 char raw text from the beginning of the page used for the RSS feed
publisher	—	string	not used
contributor	—	array	a list of all users who have made non-minor contributions to the page; every item has the user ID as key and the full name as value
date	created, valid, available, issued, modified	array	a timestamp (or an array of the timestamps <code>start</code> and <code>end</code> for a period); <code>date created</code> is filled with the creation date by default, <code>date modified</code> with the date of the last non-minor edit; the rest is not set by default

Element	Child Elements	Type	Comments
type	—	string	not set, but defaults to «text» when exported; recommended values are: collection, dataset, event, image, interactiveresource, movingimage, physicalobject, service, software, sound, stillimage or text
format	—	string	a MIME type is expected; not set, but defaults to «text/html» when exported
identifier	—	string	a unique ID of the page; not set, but defaults to the page ID when exported
source	—	string	not used
language	—	string	a two-letter language code is expected; not set, but defaults to the chosen language for DokuWiki when exported
relation	isversionof, hasversion, isreplacedby, replaces, isrequiredby, requires, ispartof, haspart, isreferencedby, references, isformatof, hasformat, conformsto	array	each of the child elements can contain a list of pages that stand in the indicated relation to the current page; the page ID serves as key, the existence of the page as value; in references, DokuWiki keeps track of which pages are linked by the current page;
coverage	spatial, temporal	array	not used
rights	accessrights, license	array	not set, but accessrights default to «public editable», «public viewable» or «private» with respect to current ACL settings; license defaults to the Creative Commons license if set

Bugs / Feature Requests

Please report bugs or feature requests at the [Bug tracker](#).

Further Resources

- [Git Repository](#)
- [Bug Tracker](#)

Changes

- [Version upped](#) (2024/08/08 00:50)
- [Merge pull request #14 from fiwswe/fiwswe-patch-1](#) (2024/08/07 21:56)
- [Fix typo](#) (2024/08/07 20:27)
- [Merge pull request #13 from fiwswe/fix_issue_12](#) (2024/08/07 13:46)
- [remove deprecated require_once and more](#) (2024/08/06 20:28)
- [Update plugin.info.txt](#) (2021/10/16 17:22)
- [Update plugin.info.txt](#) (2021/10/16 17:22)
- [add type void in unit test](#) (2021/10/16 17:22)

Discussion

This is quite nice. I'm thinking being able to set metadata on pages would be much more useful if combined with searching facilities to then display stuff based on those searches.

Sorry but this is completely out of the scope of this plugin. — [Michael Klier](#) 2008/04/19 22:08

Perfect plugin - almost :) It seems that the feed.php of DokuWiki does not care about the META Tag. Is this a bug or a feature?

Secondly: wouldn't it be nice to be able to overwrite the «original» metadata of DokuWiki with the contents of the META Tag? Or is it out of scope?

Has this plugin gone the way of the Dodo Bird? I'd like to use it, but clicking the download link gives me a 404. — [🐼 tony baldwin](#) 2011/05/04 20:45

This should have been fixed as it is working perfectly right now. — [Olivier Humbert](#) 2015/07/25 12:31

DublinCore and plugin limitations

You should change «It is *recommended* to use [Dublin Core element names](#) as keys...» to something in the lines of «It is *mandatory* for keys of added metadata to be part of the set of allowed [Dublin Core element names](#)...»; this given that, as the DokuWiki metadata parser will only accept DublinCore keys and no custom keys, any uninformed attempt to add metadata to a page will fail miserably. I assume that's what has happened in the comment above.

You're right of course. I've changed it. — [Michael Klier](#) 2008/04/19 22:08

It's rather sad, as even through the plugin's syntax can be easily adapted to also accept http-equiv metadata (such as Refresh or Encoding), the DW parser itself will not allow it. Otherwise, thanks for this plugin. — *This comment 2008-02-10 by ryan.chapelle at [his site](#)*

Complications

Hi, I don't get the Plugin to work.[...].— *This comment 2008-05-05 by david*

I found the Error myself. It was a outdated Template that I used. ;-)— *This comment 2008-05-05 by david*

It did not work on my site (latest release - incognitek template), it did not change my pages ... How can I proceed to see what's wrong ? *This comment 2008-11-01 by Julien*

It does work right now. Is it still wrong for you ? [Olivier Humbert](#) - 2015-07-25 12:33

I wonder how to make the array definitions - is there a bug or am I doing something wrong? I tried it in PHP style because the source looked as it would be treated that way:

```
~~META:
relation haspart = array("testpage" => "1")
~~
```

and just got PHP execution errors *This comment 2009-05-22 by Marcel Lemke*

This is not how this was supposed to work, now you can use `~~META:relation haspart=testpage~~` and the plugin will automatically determine if the page exists and set the metadata appropriately. — 🐼 [Michael Hamann](#) 2015-07-24 21:50

Hi, i want to set keywords for the searchengines but it do not work ... only change the META:title will work.

What will be wrong?

```
~~META:
title      = titletext
&keywords  = keyword1 keyword2 keyword3
&audience = alle
&page-topic = topic of the pages
~~
```

This comment 2016-01-02 08:08 by Wolf

Simple patch that allows to use Metadata in your pages

```
--- syntax.php.orig 2019-08-15 16:10:59.057459368 -0400
+++ syntax.php      2019-08-16 02:29:46.258100543 -0400
@@ -43,4 +43,6 @@
     function render($mode, Doku_Renderer $renderer, $data) {
-        if ($mode == 'xhtml') {
-            return true; // don't output anything
+        if ($mode == 'xhtml') {
+            global $ID;
+            foreach($data as $key=>$value)
+                if($key && (!$value or is_array($value) &&
!current($value))) $renderer->doc .= strtr(p_get_metadata($ID, $key.'
' . ($value?key($value):'')), $data[(string) NULL]?:array());
+        } elseif ($mode == 'metadata') {
@@ -89,3 +91,3 @@
         // no special treatment for the rest
-        } else {
+        } elseif( $key && $value ) {
+            $renderer->meta[$key] = $value;
```

Now you can put to your pages something like:

```
My creator is ~~META:creator~~!  
~~META:creator  
& superadmin=Yay, page created by superadmin!  
& shyuser=0h, page created by very modest user..  
~~
```

And don't forget that DokuWiki allows you to store any custom Metadata!

—  [ann.](#) / [OÜ Narayana](#) 2019-08-16 06:55

How to use the plugin

Please read <http://forum.dokuwiki.org/post/15988> about how to use the plugin. [Rolf Hemmerling](#)
2009-12-05

From:
<https://wwoss.ru/> - **worldwide open-source software**

Permanent link:
<https://wwoss.ru/doku.php?id=wiki:plugin:meta>

Last update: **2026/01/18 20:04**

